



| | | | |
|------|------|------|-------------|
| IP92 | IP91 | IP90 | IP90T Data |
| 0 | 0 | 0 | R20 (40404) |
| 0 | 0 | 1 | RX1 |

| | | | | | | |
|-----|-------|-------|--------|--------|------|----------------|
| No. | OCKS1 | OCKS0 | ACKR01 | ACKR02 | Xtal | di (mm) |
| 0 | 0 | 0 | 0 | 0 | 2500 | L 2500 96 kHz |
| 1 | 1 | 0 | 0 | 0 | 2500 | L 2500 96 kHz |
| 2 | 1 | 0 | 1 | 0 | 5120 | L 5120 48 kHz |
| 3 | 1 | 0 | 1 | 0 | 5120 | L 5120 48 kHz |
| 4 | 1 | 0 | 1 | 1 | 2500 | L 2500 192 kHz |

| | | | |
|------|------|----------------|----------------------|
| XTL1 | XTL0 | Xtal Frequency | 寄字信号模式 |
| L | L | 11.2896MHz | L L Sharp roll-off |
| L | H | 12.2880MHz | L H Slow roll-off |
| H | L | 24.5760MHz | H L Slow roll-off |
| H | H | | H H Slow delay Sharp |

(Use channel status)

| | | |
|-------|--------------|-----------|
| Title | | |
| Size | Number | Revision |
| A2 | | |
| Date: | 21-Dec-2013 | Sheet of |
| File: | 05-2013-1346 | Drawn By: |