

Thiele-Small parameters

Fs: 33 Hz
Mmd: 21.3952 grams
Mms: 27.1422 grams
Cms: 0.857 mm/N
Rms: 0.7252 kg/s
Vas: 262 liter
Xmax: ± 4 mm
Sd: 464 cm²
Re: 7.4 Ohm
Le: 1 m.H
Bl: 9.9577 T·m
Qms: 7.76
Qes: 0.42
Qts: 0.3984
no: 2.1741 %
SPL: 95.37 dB-1W/1m
SPL: 95.71 dB-2.83V/1m

Thiele-Small parameters

Fs: 36 Hz
Mmd: 45.8932 grams
Mms: 57.7981 grams
Cms: 0.3382 mm/N
Rms: 2.1862 kg/s
Vas: 273 liter
Xmax: ± 3.5 mm
Sd: 754 cm²
Re: 6.5 Ohm
Le: 1.2 m.H
Bl: 14.0579 T·m
Qms: 5.98
Qes: 0.43
Qts: 0.4012
no: 2.8727 %
SPL: 96.58 dB-1W/1m
SPL: 97.48 dB-2.83V/1m

Thiele-Small parameters

Fs: 38.4 Hz
Mmd: 45.8791 grams
Mms: 57.784 grams
Cms: 0.2973 mm/N
Rms: 2.063 kg/s
Vas: 240 liter
Xmax: ± 3.5 mm
Sd: 754 cm²
Re: 6.5 Ohm
Le: 1 m.H
Bl: 13.9752 T·m
Qms: 6.758
Qes: 0.464
Qts: 0.4342
no: 2.8403 %
SPL: 96.53 dB-1W/1m
SPL: 97.44 dB-2.83V/1m

SCW300-for bassreflex

SCW400-for open baffle

SCW400-for bassreflex

